



- CPD15/16/18SQ-GB1/GB2(P); CPD18/20SQ-GD1/GD2(P)
- Extra leg room
- Wideview mast
- Hydraulic levers next to the hood
- Standard hydraulic hose and fitting


Electric Lift Trucks

3 Wheel - Front Wheel Drive - 3000 to 4000lbs

The main parameter

MODEL	CPD15	CPD16	CPD18	CPD20	CPD18
Engine type	Electric	Electric	Electric	Electric	Electric
Battery Voltage/Rated capacity	48/440 V/Ah	48/600 V/Ah	48/720 V/Ah	48/720 V/Ah	48/600 V/Ah
Total Approximate Weight (without battery)	6614 / 4960 pounds	7055 / 5071 pounds	7385 / 5071 inch	7606 / 5291 pounds	7275 / 5291 pounds
Outside Turning Radius	58 inch	58 inch	67 inch	67 inch	58 inch
Length To Fork Face	73 inch	77 inch	81 inch	81 inch	77 inch
Mast Tilt Angle, F/R	5/7°	5/7°	5/7°	5/7°	5/7°
Wheelbase	51 inch	55 inch	59 inch	59 inch	55 inch
Load Capacity	3307 pounds	3527 pounds	3858 pounds	4409 pounds	3858 pounds
Configuration Number	SQ-GB2	SQ-GB2	SQ-GD2	SQ-GD2	SQ-GB2
Overhead Guard Height	80 inch	80 inch	80 inch	80 inch	80 inch
Overall width	42 inch	42 inch	40 inch	40 inch	44 inch
Load Center	20 inch	20 inch	20 inch	20 inch	20 inch
Standard Lift Height	130 inch	130 inch	130 inch	130 inch	130 inch

CONTACT INFORMATION



Lift North America Inc.
 Address 6180 Ordan Dr, Mississauga,
 ON L5T 2B3
Contact Person: Derek Radford
Email: derek@liftnorthamerica.com
Phone: [416 456 4668](tel:4164564668)