



This compact and flexible scrubber dryer can be used for variable applications. A low – noise cleaning is in both directions possible. Special features of the machine are the hinged push handle and the easily removable tanks, which can be carried with an ergonomic handle. The tanks can also be filled at low wash basins. The brushes and squeegees can be changed within a few seconds without any tools.

Equipment

- **Roller brush**
- **2-tank system**
- **Mains operation**
- **Variable contact pressure**
- **Transport wheels**
- **Two squeegees, straight**

Compact SCRUBBER DRIER BR 40/10 C Adv

The main parameter

Working width of brushes (mm)	400
Working width, vacuuming (mm)	400
Rated input power (W)	max. 1100
Fresh/dirty water tank (l)	10 / 10
Brush contact pressure (g/cm ²)	100 - 200
Brush speed (rpm)	650
Max. area performance (m ² /h)	400
Practical area performance (m ² /h)	300
Sound pressure level (dB(A))	71
Current type (V/Hz)	120 / 60
Weight (with accessories) (kg)	30
Weight without accessories (kg)	35.8
Dimensions (L x W x H) (mm)	520 x 470 x 1150

CONTACT INFORMATION



Lift North America Inc.
Address 6180 Ordan Dr, Mississauga,
ON L5T 2B3
Contact Person: Derek Radford
Email: derek@liftnorthamerica.com
Phone: [416 456 4668](tel:4164564668)