



PRODUCT FEATURES

- CPYD20/25/30/32C-M2H; CPYD20/25/30/32C-KU1H
- Rubber floor carpet
- Large grab handle
- Tilt steering
- Front and rear LED lighting
- Rear working light
- Rear grab handle with Horn button
- Full Aluminum Radiator
- Full Suspension Seat with adjustable arm rest and seat belt
- Operators presence switch
- Back up alarm, Mirrors
- Approved ANSI B56.1 Overhead Guard
- 2 stage 3000mm (118")

IC Cushion Tires Forklift

IC - LPG Engine - Cushion Tyres - 4000 to 7000lbs

The main parameter

MODEL	CP(Q)YD20C	CP(Q)YD25C	CP(Q)YD30C	CP(Q)YD32C
Operation model	Seated	Seated	Seated	Seated
Engine type	LPG / Dual Fuel	LPG / Dual Fuel	LPG / Dual Fuel	LPG / Dual Fuel
Max. Lifting height	185 inch	185 inch	185 inch	185 inch
Configuration Number	M2H	M2H	M2H	M2H
Overall width	42 inch	42 inch	44 inch	44 inch
Overall length (without forks)	92,5 inch	94,5 inch	97,8 inch	99 inch
Load Center	24 inch	24 inch	24 inch	24 inch
Rated Capacity	4000 pounds	5000 pounds	6000 pounds	6500 pounds

CONTACT INFORMATION



Lift North America Inc.
Address 6180 Ordan Dr, Mississauga,
 ON L5T 2B3
Contact Person: Derek Radford
Email: derek@liftnorthamerica.com
Phone: [416 456 4668](tel:4164564668)