


PRODUCT FEATURES

- Electric power steering
- AC drive controller and DC hydraulic unit
- Adjustable straddles
- Stabilizer sealed wheel
- 24-volt side loaded battery

Pallet Jacks and Stackers

Electric Stacker - Straddle - 3000-3500lbs

The main parameter

MODEL	CDD14	CDD16	CDD16	CDD16	CDD16
Controller	CURTIS	CURTIS	CURTIS	CURTIS	CURTIS
Lift motor	DC3 kW	DC3 kW	DC3 kW	DC3 kW	DC3 kW
Steering motor	DC 0.15 kW	DC 0.15 kW	DC 0.15 kW	DC 0.15 kW	DC 0.15 kW
Drive motor	AC 1.5 kW	AC 1.5 kW	AC 1.5 kW	AC 1.5 kW	AC 1.5 kW
Mast type	Standard 2-Stage	Standard 2-Stage	Full free 3-stage	Full free 3-stage	Full free 3-stage
Type	Wide legs	Wide legs	Wide legs	Wide legs	-
Fork Size (thickness/width/length)	1.5 / 4 / 42 inch	1.5 / 4 / 42 inch	1.5 / 4 / 42 inch	1.5 / 4 / 42 inch	1.5 / 4 / 42 inch
Overall length	79 95 inch	79 95 inch	82 98 inch	82 98 228 inch	75 inch
Operator type	Walkie / Stand On	Walkie / Stand On	Walkie / Stand On	Walkie / Stand On	Walkie
Engine type	Electric	Electric	Electric	Electric	Electric
Battery Voltage/Rated capacity	24/280 V/Ah	24/280 V/Ah	24/280 V/Ah	24/280 V/Ah	24/270 V/Ah
Load Capacity	3086 pounds	3527 pounds	3527 pounds	3527 pounds	3527 pounds
Configuration Number	920	D920	960	360	960H
Overall width	3241 inch	3241 inch	3241 inch	3241 inch	31.5 inch
Load Center	24 inch	24 inch	24 inch	24 inch	24 inch
Standard Lift Height	55 79 98 118 130 142 157 inch	55 79 98 118 130 142 157 inch	146 153.5 165 177 185 197 inch	209 216.5 inch	146 153.5 165 177 185 197 inch

CONTACT INFORMATION



Lift North America Inc.

Address 6180 Ordan Dr, Mississauga,
ON L5T 2B3

Contact Person: Derek Radford

Email: derek@liftnorthamerica.com

Phone: [416 456 4668](tel:4164564668)